



BRICK AND TILE SAWS

TS 351 TS 351-45

- Bevel cutting is quickly set up by rotating the machine head from 90° to 45° (only TS 351-45).
- Light and portable and include 2 wheels - for easy transportation.
- Heavy gauge jig welded frame - ensures maximum rigidity for precision cutting.
- Conveyor cart mounted on 6 sealed bearings - ensures stability and accuracy of cut.
- Adjustable cutting guide - for cutting at various angles.
- Circulating water system by electric submersible pump - for diamond blade cooling.
- Resetable thermal overload - protects motor from overheating.
- Carrying handles - for convenient lifting and moving.
- No-Volt safety switch prevents dangerous starting after electric power failure.
- Height adjustable legs allows stable positioning of machine even on uneven surfaces.



EURO
SHATAL

Simply built stronger

Murervej 5, DK-6710 Esbjerg V, DENMARK (P.O.B. 3024) Tel: +45 75 168411
Fax: +45 75 168412 E-mail: euroshatal@shatal.com www.shatal.com



BRICK AND TILE SAWS

TS 351 TS 351-45



Simply built stronger

SPECIFICATIONS

Model	TS 351	TS 351-45
Max. blade capacity (mm)	350	350
Electric motor (HP)	3HP 230V / 2HP 110V / 3HP 380V	
Cutting length (mm)	600	600
Cutting depth* (mm)	105-210*	105-210*
Dimensions LxWxH (mm)	1130 x 570 x 540	1130 x 570 x 540
Weight (kg)	72	73

*By reversing material.



Simply built stronger

Sold and Serviced by:

* SPECIFICATIONS AND FEATURES ARE SUBJECT TO CHANGE WITHOUT NOTICE.

03042000

